



espresso specialisten

KVALITETSUTSTYR FOR LIDENSKAPELIGE BARISTAER

	Strada MP		Strada EP	
Versions	2 group	3 group	2 group	3 group
Width	800mm (circa)	1000mm	800mm (circa)	1000mm
Height	450mm		450mm	
Depth	660mm		660mm	
Weight	70kg (circa)	90kg	70kg (circa)	90kg
Voltage	220V (1 phase) 380V (3 phase)		220V (1 phase) 380V (3 phase)	
Max. power	4600w	6400w	4600w	6400w
# Coffee boilers	2 (1 per group)	3 (1 per group)	2 (1 per group)	3 (1 per group)
C. boiler capacity	1.3 liters (each)		1.3 liters (each)	
# Steam boilers	1		1	
S. boiler capacity	8.2 liters	11.8 liters	8.2 liters	11.8 liters
# Pumps	1		2	3
Pump type	Rotary		Gear	
Pump positior	External		Internal	
# Pre-heaters	1		1	
# Water inlets	2		2	
Paddle interface	Mechanical		Electronic	
# Steam wands	2		2	
Wand control	Lever (articulated)		Lever (articulated)	
Hot water tap	Yes (with mixing valve for temp. control)		Yes (with mixing valve for temp. control)	
Groups & boilers	Stainless steel		Stainless steel	
Brew groups	Saturated		Saturated	
Body	Stainless steel (polished)		Stainless steel (polished)	
Sides	Cast aluminum		Cast aluminum	
Side panels	Stainless Steel (polished)		Glass (tempered)	
Strada logo				
Color sides	Black		Black	
Color details	Black		Black	
Drain tray	Adjustable (2 positions)		Adjustable (2 positions)	
Pore filters	Stainless steel (snap on)		Stainless steel (snap on)	
Shot timer	Digital (1)		Digital (1 per group)	
Temp. display	Digital (1)		Digital (1 per group)	
Pressure display	Analogical gauge (1 per group)		Digital (1 per group)	
Programming	Jog wheel control		Jog wheel control	
Temp. control	P.I.D. (electronic)		P.I.D. (electronic)	
Pump speed	Fixed		Variable	
Pressure range	0 - 9 bar		0 - 12 bar	



